

LUX BITOLA® Cappucino Espresso Machines



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description JP.CPC.2G

- 230 V operating voltage.
- Double steam arm.
- Dosage adjustment unit.
- 2 double filter handles.
- 10.5 liter boiler capacity.
- Extra-warm water arm.
- Semi automatic.

JP.CPC.3G

- 230 V operating voltage.
- Double steam arm.
- Dosage adjustment unit.
- 3 double filter handles.
- 17 liter boiler capacity.
- Extra-warm water arm.
- Semi automatic.

JP.CCG.01

- 230 V - 356 W-1.75 A
- Thermal motor protection equipment.
- Maximum operating time 30 minutes.
- Mill diameter of 60 mm
- Bin capacity 2 kg
- Dispenser average of 2 kg capacity.

Co	Descriptio	Dimensions	We Net	Ca
----	------------	------------	--------	----

Import Products : LUX BITOLA®; Cappucino Espresso Machines

de n	a	b	mm c				ight m3 kg	pac ity lt
JP. Capuccino CP Espresso C.2 Machines G 2 Groups	710x545x528			72.5	0.20	10.5		
JP. Capuccino CP Espresso C.3 Machines G 3 Groups				110	0.20	17		
JP. Coffee CC Grinder G.0 1				9	0.04	2		
JP. Water SF. Filters 01	230x230x520			6	0.2	12		

Reviews

There are yet no reviews for this product.