

LUX BITOLA® Cold Service Units



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description

- Capacity for 3 door refrigerator:10 pieces of 1/4-150 gastronorm container.
- Capacity for 4 door refrigerator:10 pieces of 1/4-150 gastronorm container.
- Fermentation drawer capacity: 2 pieces 400x600 mm.
- Tray grid capacity: 4 pieces 400x600 mm for each.
- Working temperature: +0 ° C , + 5 ° C (at ambient temp. 43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- "CFC Free" , 404 A refrigerated gas.
- 40 kg/m3 yogunluk.
- Elektronik temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable, conditioning compresor.
- Fan cooling.
- "Ozone - Friendly" 48 mm thickness polyurethane isolation.
- Self closing doors.
- Copper tube evaporator with aluminum fins.
- Adjustable, stainless steel shelf housing, plastic coated shelves.
- Led lighting.
- Optional Wooden front surface.

CD	Dimensions	NPC
oe	mm	ea
ds		twp
ec		ea

ri	a	b	c
p			
ti			
o			
n			

k	r	ci
g	k	ty
	w	lt

ER21002105
e x8807 . . 0
fr x8500540
ig 75
e
r
a
t
e
d
C
ol
d
S
e
r
vi
c
e
U
ni
t
(
T
ri
pl
e
D
o
o
r
s
)
ER26503107
e x8801 . . 0
fr x8500950
ig 8
e
r
a
t
e
d
C
ol
d
S
e
r
vi
c
e
U
ni
t
(
F
o
u
r
D
o
o
r
r

s
)

Reviews

There are yet no reviews for this product.