

LUX BITOLA® Display Units - Cold & Hot



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

- Description **DISPLAY UNIT - COLD**
- 220V / 50hz electrical power.
 - Working temperature: 0°C + 12°C
 - R-134 A refrigerant gas.
 - Led lighting system.
 - Double glass.
 - 2 adjustable shelves.
 - Digital temperature control.

- DISPLAY UNIT - HOT**
- 220 V - 50Hz. Energy.
 - Led lighting system.
 - Thermostatic control.
 - 3 adjustable shelves

Co de	Descriptio n	Dimensions mm				We ight kg	Po wer kw	Net m3	Ca pac ity lt
		a	b	c					
JP.	Display	702x568x686		64	0.1	0.2	120		
120	Unit - Cold				6	0			
.S									
JP.	Display	880x568x686		71	0.1	0.3	160		
160	Unit - Cold				6	0			
.S									

JP. Display 120 Unit - Hot .l	678x578x670	48	1.1	0.2	120
				0	
JP. Display 160 Unit - Hot .l	857x578x670	56	1.5	0.3	160
				0	

Reviews

There are yet no reviews for this product.