

LUX BITOLA® Refrigerated Cabinets (Static Cooling)



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description

- For single door; 3 pieces GN 2/1 interior shelves.
- For double doors; 6 pieces GN 2/1 interior shelves.
- Working temperature; 0° C , + 5° C (at ambient temp. 43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- "CFC Free" , R-134 A gas.
- 40 kg/m3 density.
- Electronic temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable, conditioning compressor.
- Static cooling.
- "Ozone-friendly" 48 mm thickness polyurethane isolation.
- Self closing doors.
- Copper tube evaporator with aluminum fins.
- Stainless steel body.

Code	Description	Dimensions mm			Weight kg	Net m3	Power kw	Capacity lt
		a	b	c				
EMP.70.80.01- STA	Refrigerated Cabinets (Single Door)		700x800x2050		130	1.2	0.4	700
EMP.140.80.0	Refrigerated		1400x800x2050		220	2.4	0.6	1400

1-STA Cabinets (
Double Door)

Reviews

There are yet no reviews for this product.