



[Ask a question about this product](#)

- 220 V-230 V -1 +N -50 60 Hz electrical power.
- "CFC Free" , R-134 A refrigerant gas.
- 40 kg/m3 density.
- Electronic temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable, conditioning compressor.
- Cooling with fan.
- "Ozone-friendly" 48 mm thickness polyurethane isolation.
- Self closing doors .
- Rounded front top edges.
- Copper tube evaporator with aluminum fins.
- Adjustable, stainless steel shelf housing, plastic coated shelves.
- Stainless steel body.

CD	Dimensions				NPC
oe	mm				eo a
ds a b c					t w p
ec					e a
ri					k r c
p					g kty
ti					w l t
o					
n					

ER 1500 8 0 0 2
e x600 5 . . 5
fr x850 8 3 0

ig 5
e
r
a
t
e
d
C
o
u
n
t
e
r
(
D
o
u
bl
e
D
o
o
r
s
)
ER15009003
e x7005 . . 0
fr x850 930
ig 5
e
r
a
t
e
d
C
o
u
n
t
e
r
(
D
o
u
bl
e
D
o
o
r
s
)
ER20001104
e x6001 . 0
fr x850 0 30
ig 5
e
r
a
t
e
d
C
o
u
n

t
e
r
(
T
ri
pl
e
D
o
o
r
s
)
ER20001105
e x7002 . . 0
fr x8500230
ig 5
e
r
a
t
e
d
C
o
u
n
t
e
r
(
T
ri
pl
e
D
o
o
r
s
)
ER25501105
e x6003 . . 5
fr x8505350
ig 0
e
r
a
t
e
d
C
o
u
n
t
e
r
(
F
o
u
r
D
o
o
r
s
)

)
ER 2550 1 1 0 7
e x700 4 . . 0
fr x850 5 5 5 0
ig 0
e
r
a
t
e
d
C
o
u
n
t
e
r
(
F
o
u
r
D
o
o
r
s
)

Reviews

There are yet no reviews for this product.