

LUX BITOLA® Refrigerated Counters (Static Cooling)



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

- Description - Working temperature; 0° C , + 5° C (at ambient temp.43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
 - “CFC Free”, R-134A refrigerant gas.
 - 40 kg/m3 density.
 - Electronic temperature and defrosting control and display.
 - Automatic evaporation of water during defrosting.
 - Removable,conditioning compressor.
 - Static cooling.
 - “Ozone-friendly” 48 mm thickness polyurethane isolation.
 - Self closing doors.
 - Rounded front top edges.
 - Copper tube evaporator with aluminum fins.
 - Adjustable,stainless steel shelf housing,plastic coated shelves.
 - Stainless steel body.

Dimensions				NPC
mm				
CD	oe	ds	a b c	ea
				t wp
				ea
				r ci
				k ty
				g wlt
ER	1500	900	2	
e	x600	5	5	
fr	x850	830		

ER 1500 1 0 0 3
e x700 0 . . 0
fr x850 5 9 3 0
ig 5

t
e
r
(
T
ri
pl
e
D
o
o
r
s
)
ER20001105
e x7003 . . 0
fr x8500230
ig 5
e
r
a
t
e
d
C
o
u
n
t
e
r
(
T
ri
pl
e
D
o
o
r
s
)
ER25501105
e x6004 . . 5
fr x8505350
ig 0
e
r
a
t
e
d
C
o
u
n
t
e
r
(
F
o
u
r
D
o
o
r
s
)

)
ER 2550 1 1 0 7
e x700 5 . . 0
fr x850 5 5 5 0
ig 0
e
r
a
t
e
d
C
o
u
n
t
e
r
(
F
o
u
r
D
o
o
r
s
)

Reviews

There are yet no reviews for this product.