

LUX BITOLA® Cold Service Units (Refrigerated)



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description - Working temperature; 0° C , + 5° C (at ambient temp. 43° C)

- 220 V-230 V -1 +N -50 60 Hz electrical power.
- 404 A refrigerant gas.
- 40 kg/m3 density.
- Electronic temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable,conditioning compressor.
- Cooling with fan.
- "Ozone-friendly" 48 mm thickness polyurethane isolation.
- Self closing doors.
- Copper tube evaporator with aluminum fins.
- Adjustable,stainless steel shelf housing,plastic coated shelves.
- Optional wooden front surface.
- Led lightining.
- Stainless steel body.

Dimensions				NPC
mm				
CD	oe	ds	a b c	ea
				tw
				ea
				rci
				g kty
				w

EC 1250 8 0 0 3
olx790 6 . . x

d x850 8 3 1
S 5 /
e 1
r G
vi N
c
e
U
ni
t
-
R
e
fr
ig
e
r
a
t
e
d
EC15001104
olx790 0 . x
d x850 0 4 1
S 5 /
e 1
r G
vi N
c
e
U
ni
t
-
R
e
fr
ig
e
r
a
t
e
d
EC20001105
olx790 2 . . x
d x850 0 2 4 1
S 5 /
e 1
r G
vi N
c
e
U
ni
t
-
R
e
fr
ig
e
r
a
t
e
d
EC25551106
olx790 4 . . x

dx8500651
S8 /
e1
rG
viN
c
e
U
ni
t
-
R
e
fr
ig
e
r
a
t
e
d

Reviews

There are yet no reviews for this product.