

LUX BITOLA® Electric Combi Ovens



Rating: Not Rated Yet
Price:
Variant price modifier:

Base price with tax:
Price with discount:
Salesprice with discount:
Sales price:
Sales price without tax:
Discount:
Tax amount:

[Ask a question about this product](#)

- Description - 400 V. 50 Hz operation power.
- ECO function for consumption reduction in cooking.
 - SC2 semi automatic washing.
 - Cooking modes: manual or programmable selection, 99 programs with 4 phases of whom 7 are standard, 3 re-heating programs, 5 smoking, 4 Low Temperature and 1 Delta T.
 - Single-point temperature core probe.
 - UR2 automatic humidity control while cooking.
 - RDC steam generator with low management cost.
 - Automatic fan reverse AWC, 2 fan speeds.
 - Digital controls.
 - Manual steam injection.
 - Self-diagnosis with malfunction alarms.
 - IPX5 protection degree.
 - Door double tempered glazing.
 - AISI 304 stainless steel polished cooking chamber ,with AISI 316L (1,2 mm) top and bottom and rounded edges without joints.
 - Handle with double handgrip, easier opening also with hands full.
 - Automatic Cooling and Preheating.
 - Start-up time selection.
 - Display of set and current cooking values.
 - Low temperature steam and Superheated steam.

CD	Dimensions	NPL
oe	mm	eo o
ds		t wa
ec		edi

ri	a	b	c
p			
ti			
o			
n			

k	r	n
g	kg	
	wC	
	a	
	p	
	a	
	ci	
	ty	
	p	
	o	
	rt	
	io	
	n	

EE 920x 1 1 1 8
le874x 6 0 5
ct 730 0 .
ri 1
c
G
a
s
C
o

EB 740x 2 0
o 850x 5 .
tt 700 4
o 5

EE 920x 1 1 1 1
le874x 9 . 7 4
ct 975 8 2 . 0
ri 3
c
C
o

EB 700x 3 0
o 860x 0 .
tt 600 3
o

ES 230x 5 0 0
355x . . .
120 2 0 1
1 5

Reviews

There are yet no reviews for this product.