

LUX BITOLA® Freezer Cabinets (Static Cooling)



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description

- For single door; 3 pieces GN 2/1 interior shelve.
- For double doors; 6 pieces GN 2/1 interior shelve.
- Working temperature for freezers;-18° C,-20° C
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- “CFC Free” , 404A gas.
- 40 kg/m3 density.
- Electronic temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable,conditioning compressor.
- Static cooling.
- "Ozone-friendly" 48 mm thickness polyurethane isolation.
- Self closing doors.
- Copper tube evaporator with aluminum fins.
- Stainless steel body.

CD	Dimensions	NPC
oe	mm	eo a
ds		t w p
ec		ea
ri		k r ci
p		g k ty
ti		w lt
o		

n a b c

EF 700x 1 1 1 7

r 800x 4 . 0

e 2050 5 2 0

e

z

e

r

C

a

bi

n

e

ts

(

S

in

gl

e

D

o

o

r)

EF 1400 2 2 1 1

r x800 4 . . 4

e x205 5 4 3 0

e 0 0

z

e

r

C

a

bi

n

e

ts

(

D

o

u

bl

e

D

o

o

r)

Reviews

There are yet no reviews for this product.