

LUX BITOLA® Hot - Cold Banquet Trolley



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description

- One modul operates cold one modul operates hot.
- Operating voltage : 220 V
- Digital thermostat control unit.
- Interior heating indicator.
- Humiditication system.
- Working temperature; 0° C, + 5° C (at ambient temp.43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- "CFC Free" , R-134 A refrigerant gas.
- Digital thermostat control unit.
- Magnetic locker.
- Lockable castors provide stabilizing.
- Isolation type:40 kg/m3 density polyurathane isolation.
- Pressed interior tray slides.
- Stainless steel body.

CD	Dimensions	NPC
oe	mm	eo a
ds		t wp
ec		ea
ri		k r ci
p		g kty
ti		w

o a b c
n



EH1352 2 2 4 2
o x888 2 . . x
t x180 0 1 1 (
- 3 7 1
C 1
ol x
d G
B N
a 2
n /
q 1
u)
e
t
T
r
ol
le
y

Reviews

There are yet no reviews for this product.