

LUX BITOLA® Proofer



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

- Description - For Isolated cabinet; 40 kg/m3 density.
- 0°C - 90°C operating temperature.
 - 16-40x60 tray capacity.
 - Thermostatic electronic heating control setting.
 - Humidity sensor.
 - Steam resistance.
 - Manuel resistance.
 - Stainless steel body.

CD				Dimensions			NPC		
oe				mm			eo a		
ds a b c							t w p		
ec							ea		
ri							k r ci		
p							g k ty		
ti							w		
o									
n									
EP 500x 8 0 3 1									
r 720x 0 . K 6									
o 1800 7 w -									
o - 4									
f 2 0									
e 2 x									
r 0 6									
(V 0									

S
in
gl
e
J
a
c
k
e
t)
EP 500x 8 0 3 1
r 720x 3 . K 6
o 1800 7w -
o - 4
f 2 0
e 2 x
r 0 6
- V 0

EP 630x 9 1 3 1
r 850x 3 . K 6
o 1900 0w -
o 2 - 4
f 2 0
e 2 x
r 0 6
(l V 0
s
ol
a
t
e
d
)
EP 630x 9 1 3 1
r 850x 6 . K 6
o 1900 0w -
o 2 - 4
f 2 0
e 2 x
r 0 6
- V 0

Reviews

There are yet no reviews for this product.