

LUX BITOLA® Refrigerated Cabinets (Fan Cooling)



Rating: Not Rated Yet
Price:
Variant price modifier:

Base price with tax:
Price with discount:
Salesprice with discount:
Sales price:
Sales price without tax:
Discount:
Tax amount:

[Ask a question about this product](#)

Description

- 3 pieces GN 2/1 trays interior shelve.
- Working temperature; 0° C , + 5° C (at ambient temp. 43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- "CFC Free" , R-134 A gas.
- 40 kg/m3 density.
- Electronic temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable,conditioning compressor.
- Fan cooling.
- "Ozone-friendly" 48 mm thickness polyurethane isolation.
- Self closing doors.
- Copper tube evaporator with aluminum fins.
- Stainless steel body.

CD	Dimensions	NPC
oe	mm	eo a
ds		t w p
ec		ea
ri		k r ci
p		g k ty
ti		w lt



ER 700x 1 1 0 7
e 800x 3 . . 0
fr 2050 0 2 4 0
ig
e
r
a
t
e
d
C
a
bi
n
e
ts
(
S
in
gl
e
D
o
o
r)
EG 700x 1 1 0 7
la 800x 4 . . 0
s 2050 5 2 4 0
s
D
o
o
r
R
e
fr
ig
e
r
a
t
e
d
C
a
bi
n
e
ts
(
S
in
gl
e
D
o
o
r)

Reviews

There are yet no reviews for this product.