

LUX BITOLA® Refrigerated Under Counters



Rating: Not Rated Yet

Price:

Variant price modifier:

Base price with tax:

Price with discount:

Salesprice with discount:

Sales price:

Sales price without tax:

Discount:

Tax amount:

[Ask a question about this product](#)

Description

- Working temperature; 0° C , + 5° C (at ambient temp. 43° C)
- 220 V-230 V -1 +N -50 60 Hz electrical power.
- "CFC Free" , R-134 A gas.
- 40 kg/m3 density.
- Electronic temperature and defrosting control and display.
- Automatic evaporation of water during defrosting.
- Removable, conditioning compressor.
- "Ozone-friendly" 48 mm thickness polyurethane isolation.
- Smooth front top edges.
- Copper tube evaporator with aluminum fins.
- Adjustable, stainless steel shelf housing, plastic coated shelves.
- Stainless steel body.

CD oe ds ec ri p ti o n	Dimensions mm			NPC eo a t wp ea r ci k g kty wlt
	a	b	c	
ER 1600 9 0 0 4				
e x600 5 . . x				

fr x550 5 3 2
ig 5 /
e 3
r 2
a 0
t 0
e
d
U
n
d
e
r
C
o
u
n
t
e
r
ER2000 1 0 0 6
e x600 1 . . x
fr x550 0 6 3 2
ig 5 /
e 3
r 2
a 0
t 0
e
d
U
n
d
e
r
C
o
u
n
t
e
r
ER1600 9 0 0 4
e x700 0 . . x
fr x550 6 3 1
ig 5 /
e 1
r 2
a 0
t 0
e
d
U
n
d
e
r
C
o
u
n
t
e
r
ER2000 1 0 0 6
e x700 2 . . x
fr x550 0 8 3 1
ig 5 /
e 1

r	2
a	0
t	0
e	
d	
U	
n	
d	
e	
r	
C	
o	
u	
n	
t	
e	
r	

Reviews

There are yet no reviews for this product.